



ТЕХНОЛОГИИ СЕТЕЙ
ВСЕ ДЛЯ ПОСТРОЕНИЯ СЕТЕЙ

TYPE		MODEL NAME	
EPON ONU		GCOM ONU E110G	DESCRIPTION
SPECIFICATION	Chipset	CPU	ZX279125
		FLASH	128Mbit SPI flash
		RAM	64 Mbit DDR2(On-chip)
	Interfaces	LAN port	1 * GE port
	EPON	Standard	IEEE 802.3ah, YD/T 1475-2006
		Wavelength	1310nm/1490nm
		Speed	Upstream rate up to 1.244 Gbit/s, downstream rate up to 1.244 Gbit/s
		Sensitivity	≤-27dBm
		Emission Power	0.5dBm≤P≤4dBm
		Distance	20 km
		Connector	SC/UPC; SC/APC
		Support	Protocols
	Access Mode		PPPoE, Bridge, IPOE, (Optional)
	Security	Management	OAM
		Algorithm	SP/WRR/SP+WRR
		Encryption	AES128、Triple Churning
	Accessories	Authentication	CHAP, EAP
		Others	Loopback
			1 * Power Adpter
	Device Parameter		1 * Manual
		Power Suply	Input 110~240VAC; Output 12V DC/1A
		Power Consumption	2.5W
		Net Weight	55g
		Size	74mm(L) ×74mm(W) ×20mm(H)
			